



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

C45-K-HC
Job Sheet 171900



Part No: C45-K-HC

Job Qty: 1 ea

Part Name: C-Series Remote Hook 4,500 lbs Lift Capacity - Keeperless With Cage



Part Weight: 0 lbs

Status: Scheduled

Priority: Medium

Job Created: 2/9/18

Job Tracking No:

Due Date: 2/9/18

Created By: Linda Lacelle

Type: SOLD

Description:

Ship Via:

*No Rev. / No Dwg.
Kit composed of C45-K and C45-C*

Bill of Materials

Job Routing

Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Sign-off
					Setup hrs	Run Hrs	Workcenter / Supplier	Lead Time	
90	Start up Operation	1 Ea	2/9/18	2/9/18	0.00	0.00	Start Up Machining-1		<i>SLB</i>
110	QC	1 pcs	2/9/18	2/9/18	0.00	0.00	QC5		<i>38</i>
120	Packaging	1 pcs	2/9/18	2/9/18	0.00	0.00	Packaging3		<i>9-88 352</i>
130	QC21-FG	1 Ea	2/9/18	2/9/18	0.00	0.00	QC21		<i>DAS 21 9-88</i>

Job BOM

Part / Item	Component Name	Quantity	Operation	Container
C45-CP	C45 Cage	1 pcs (1 ea)	90-Start up Operation	<i>5029339</i>
C45-Loaner	C-Series Remote Hook 4,500 lbs Lift Capacity	1 Ea (1 ea)	90-Start up Operation	<i>5040856</i>

Job Allocations

Operation	Component Part	Required	Inventory	Allocated
90-Start up Operation	C45-CP	1	3	0
	C45-Loaner	1	2	0

Part Specifications

Specifications could not be found.



S040860



C-Series Remote Hook 4,500 lbs Lift Capacity
With Cage
PART NO:
Original Serial #:
Revision:
Operation:
Change No:

C45-K-HC
S040860

Start up Operation
Keeperless

Job No: 171900
02/09/18

Dart Aerospace Ltd
1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
CANADA
TEL: 1 613 632-5200
Email: sales@dartaero.com
www.dartaerospace.com



Remote Cargo Hook Test Form

C45

Work Order 171900

Customer DART

Serial Number 3288-01

Date 2018-01-18

# of Releases	Load (Lbs.)	Release Method	Remarks	Result	Pass/fail
1	11,250	Static Hold	Hold for two Minutes and reduce load to zero	N/A	PASS
10	2,250	Electircal, 25 volts	No "hang ups" permitted	N/A	PASS
2	4,500	Electircal, 22 volts	Current shall not exceed 12.4A 9.2 10.5 A	9.2 A	PASS
2	3,500	Electircal, 22 volts	Current shall not exceed 12.4A 9.2	9.2 A	PASS
2	2,500	Electircal, 22 volts	Current shall not exceed 12.4A	9.2 A	PASS
2	1,500	Electircal, 22 volts	Current shall not exceed 12.4A	9.2 A	PASS
2	500	Electircal, 22 volts	Current shall not exceed 12.4A	9.0 A	PASS
1	4,500	Electircal, 20 volts	Current shall not exceed 11.3A	8.2 A	PASS
1	4,500	Electircal, 28 volts	Current shall not exceed 15.8A	11.5 A	PASS
1	4,500	Manual		N/A	PASS
1	4,500	Impact Test	Impact shackle 10 times, shall not release	N/A	PASS
1	N/A	Solenoid Ohms	Shall not exceed 1.7-2.0 Ohms	2.0 Ohms	PASS
1	N/A	Electircal Continuity	Across both wires	N/A	PASS

Test Conducted By: ALAIN PATRY
Technician

Signature: [Signature]
Director Of Quality Assurance

Submit